

ecoprox



Ecoprox spray cork is a durable color finish for interior and exterior use. A flexible cork-based coating that offers many beneficial properties such as thermal and acoustic insulation, sound absorption, moisture resistance, fire retardancy and extreme durability.

Processing Instructions:

Mechanically applied with a spray gun (compressed air and/or industrial compressor).
Minimum of two coats.



Coverage:
7 m² in 2 layers

- Touch dry 1 - 2 hours (temp 20°C)
- Total drying 12 - 24 hours (temp 20°C)
- Processing temperature 5°C - 35°C
- Thickness 3 mm in 2 layers



Recommendations

- The surface must be clean be dust-free and dry
- The product should be stored in well-ventilated rooms, protected from sunlight, water and frost, at temperatures between 5°C and 30°C.

Shelf life : 12 months
from the date of
production

	Layer 1	Layer 2
Distance	+/- 40/50 cm	+/- 70 cm
Temperature	5°C - 30°C	5°C - 30°C
Bar	4,0 - 4,5	4,0 - 4,5
Quantity	Min 1 kg/m ²	Min 0.7 kg/m ²

Ecoprox BV

Londerzeelsesteenweg 34
1861 Meise

+32 (0)2 609 53 75
info@ecoprox.eu

